



Preparador de Pedidos JX2-1 Order Picker 0,7t. Preparador de Pedidos JX2-4 Order Picker 1,0t.

- Diseño compacto de nivel medio tanto para el picking de cajas como para el manejo de pallets.
- Sistema de elevación dual, vista operativa más amplia.
- Order Picker JX2 funciona con un motor de CA de alta eficiencia y se puede programar a través del panel LCD integrado.
- Altura máxima de elevación es de hasta 3620 mm.
- El modelo JX2-4 está construido para levantar hasta 1 tonelada.
- Sistema de control sensible le brinda una sensación de trabajo suave y precisa.

Preparador de Pedidos JX2-1 Order Picker 0,7t.

Distinguishing mark	1.1	Manufacturer			EP
	1.2	Model designation			JX2-1
	1.3	Drive			Electric
	1.4	Operator type			Order-picker
	1.5	Load capacity	Q	kg	700/136
	1.6	Load center distance	c	mm	600
	1.8	Load distance □ centre of drive axle to fork	x	mm	140
	1.9	Wheelbase	y	mm	1280
	Service weight	2.1	Service weight		kg
2.2		Axle loading, laden front/rear		kg	1800/720
2.3		Axle loading, unladen front/rear		kg	700/920
Tyres/chassis	3.1	Tyre type			Polyurethane/Solid rubber
	3.2	Tyre size, front		mm	Φ150×90
	3.3	Tyre size, rear		mm	Φ230×75
	3.4	Additional wheels (castor wheels)		mm	Φ74×48
	3.5	Wheels, number front/rear (x=drive wheels)		mm	1x □ 2/2
	3.6	Tread width, front	b10	mm	710
	3.7	Tread width, rear	b11	mm	570
Dimensions	4.2	Retracted mast height	h1	mm	1510
	4.3	Free lift	h2	mm	737
	4.4	Lift height	h3	mm	1063
	4.5	Height, mast extended	h4	mm	2560
	4.7	Height of overhead guard (cabin)	h6	mm	1560
	4.8	Seat height/standing height	h7	mm	220
	4.14	Stand height, elevated	h12	mm	1220
	4.15	Lowered height	h13	mm	63
	4.19	Overall length	l1	mm	2520
	4.20	Length to face of forks	l2	mm	1605
	4.21	Overall width	b1/b2	mm	800
	4.22	Fork dimensions	s/e/l	mm	35/100/915
	4.25	Distance between fork-arms	b5	mm	560
	4.32	Ground clearance, center of wheelbase	m2	mm	50
	Performance data	4.34.1	Aisle width for pallets 1000×1200 crossways	Ast	mm
4.34.2		Aisle width for pallets 800×1200 crossways	Ast	mm	3070
4.35		Turning radius	Wa	mm	1470
5.1		Travel speed, laden/unladen		km/h	8/8
5.2		Lifting speed, laden/unladen		m/s	0.13/0.16
5.3		Lowering speed, laden/unladen		m/s	0.16/0.18
5.8		Max. gradeability, laden/unladen		%	0
Electric-engine	5.10	Service brake			Electromagnetic
	6.1	Drive motor rating S2 60 min		kW	2.5
	6.2	Lift motor rating at S3 15%		kW	3
	6.4	Battery voltage/nominal capacity		V/Ah	24/360
	6.5	Battery weight		kg	330
Addition data	8.1	Type of drive control			AC
	10.5	Steering design			Electronic
	10.7	Sound pressure level at the driver's ear		dB(A)	74

If there are improvements of technical parameters or configurations, no further notice will be given.
The diagram shown may contain non-standard configurations.

